



Speedline® 25/50 Smoke Safe™ PVC

Speedline® 25/50 Smoke Safe™ PVC Fitting Covers And Jacketing

Description:

The Speedline® Smoke Safe™ PVC Insulated Fitting Covering System consists of preformed gloss white outdoor weatherable and gloss colored insulated covers for piping fittings. Their unique shapes fit screwed, Victaulic®, welded and flanged elbows, tees, valves, couplings, laterals, reducers and end caps.

The Speedline® Smoke Safe™ PVC Jacketing System consists of gloss white outdoor weatherable and colored PVC sheet in either bulk rolls or precurled cut-to-fit pipe sizes. The Jacketing is available in .010", .015", .020", and .030" thicknesses.

The Jacketing and Fitting Covering Systems include solvent weld adhesives, stainless steel tack fasteners, silicone caulking and adhesive tapes.

A die-cut multi-temperature fiberglass insulation insert is available and sized for a full insulation over the exposed pipe fitting and under the overlay of the PVC Fitting Cover.

The Speedline® Smoke Safe™ PVC Systems are designed to cover pipe fittings and other mechanical equipment from an outside diameter of 1-5/8" to 24" in accordance with ASTM C-585.

Code Compliance:

Speedline® Smoke Safe™ PVC Fitting Covers and Jacketing meet:

Military Specification LP-1035A, Type 11 Grade GU and Type 111, and LP-535E, Type 11 Grade GU and Type 111. Federal Specification HH-I-558, Form B, Type 1 Class B Requirements of USDA and FDA for use in facilities of the food processing, beverage and pharmaceutical industries.

Advantages:

The ease of installing Speedline® Smoke Safe™ PVC Fitting Covers and Jacketing assures a uniform, neat, attractive insulation of piping fittings and other mechanical piping equipment. The high gloss PVC surface provides a cleaner, neater appearance; its surface remains more maintainably clean and highly corrosion resistant. Its outdoor weatherability (UV stable) provides greater flexibility of usage. The 25/50 fire class of all Speedline® Smoke Safe™ Products provides greater universal building code acceptance. Speedline® Smoke Safe™ PVC Fitting Covers and Jacketing provide a natural barrier to moisture, bacteria and mold; their unique shapes make an easy seal over an entire mechanical system.

Applications:



Speedline® Smoke Safe™ PVC Insulated Fitting Covers and Jacketing are designed for applications indoors or out-of-doors in commercial, institutional and industrial facilities. The system has an applicable temperature range of -35°F to 500°F (-37°C to 260°C). The PVC surface should remain below 150°F (66°C) through the installation of sufficient insulation on higher temperature applications.

• **Colored Fitting Covers and Jacketing are not recommended for outdoor usage.**

Physical Properties: Speedline® Smoke Safe™ PVC:

Property	Test Method	Value
Flame Spread	ASTM E84	25 or less
Smoke Developed	ASTM E84	50 or less
Specific Gravity	ASTM 792	1.46
Tensile Strength	ASTM D638	7,000
@ yield lb./in. ²		
Tensile Modulus	ASTM D638	400,000
PSI		
Izod Impact-ft.lb./in.	ASTM D256	15.0
Electrical	ASTM D257	None
Conductance		

Physical Properties: Fiberglass Insulation

Property	Test Method	Value
Flame Spread	ASTM E84	25 or less
Smoke Developed	ASTM E84	50 or less
Thermal Conductivity	ASTM C177	0.26
(75°F/24°C)		

Specification Data:

Hot Systems:

All piping fittings shall be insulated by filling the total void over all fittings, between straight runs of pipe insulation, with Speedline die-cut fiberglass insulation, forming a uniform insulation thickness equal to or exceeding the adjacent pipe insulation. Finish all insulated pipe fittings by applying Speedline Smoke Save PVC Fitting Covers overlapping the adjacent pipe insulation outer covering. Secure the Speedline Fitting Covers with Speedline Stainless Steel Tack Fasteners, Speedline PVC Tape or by Welding PVC overlaps with Speedline Vinyl Adhesive. Caution should be exercised to be sure that the insulation surface temperature is maintained below 150°F (66°C) through the application of sufficient insulation under all PVC Covering.

Cold Systems:

All piping fittings shall be insulated by filling the total void over all pipe fittings between straight runs of pipe insulation with Speedline die-cut fiberglass insulation, forming a uniform insulation thickness equal to, or exceeding, the adjacent pipe insulation. Finish all insulated pipe fittings by applying Speedline Smoke Safe PVC Fitting Covers overlapping the adjacent pipe insulation outer covering. The overlap of the throat of the PVC Fitting Cover and the ends of the Fitting Cover overlapping the adjacent pipe insulation vapor barrier jacketing shall be vapor sealed with compatible vapor barrier mastic. The ends of the PVC Fitting Cover overlapping the pipe insulation shall be further sealed by an outer wrapping of Speedline PVC Tape extending over the adjacent pipe insulation vapor barrier jacketing and overlapping its own juncture by at least two inches in the downward direction on the downward side.

Chemical Resistance:

Inorganic Acids:
Sulfuric, Nitric, hydrochloric, hydrofluoric (diluted or concentrated): Excellent

Organic Acids:
Formic, acetic and propionic Poor

Alkalies:
Sodium and potassium hydroxides Excellent
Ammonium hydroxide Excellent
Caustic Soda Excellent
Soda Ash Excellent

Miscellaneous Corrosive Chemicals:
Phenol, resorcinol and creosol Poor
Iodine, crystals Fair
Iodine, tincture Excellent
Chlorine and bromine water Excellent
Potassium dichromate Excellent
Silver nitrate Excellent
Tannic acid Excellent

Solvent and Dilutents:
Alcohol and polyalcohols, including ethyl methanol, butanol and isopropyl alcohol Excellent

Ketones:
Lower boiling ketones Dissolves
Higher boiling ketones Swells

Ethers:
Ethyl Softens
Dichlorethyl ether Swells
Diethyl cellosolve Swells
Dioxane Dissolves
Propylene oxide Dissolves

Hydrocarbons:
Aromatics as gasoline, kerosene and petroleum oils Excellent

Oils, Fats and Waxes:
Animal, mineral and vegetable Excellent